

# Naturals Fix


## GLUEDOWN CORK FLOOR TILES

### WEARTOP® Finish

### TECHNICAL SPECIFICATION

Distributed in the UK by Natrul | Manufactured by Granorte, Portugal

#### GENERAL DEFINITION AND PRODUCT COMPOSITION

Definition	High-density veneered cork floor tiles, 4mm thickness, interior floor covering in accordance with EN 12104.
Dimensions	<b>600 x 300 x 4 mm</b>
Finish	WEARTOP® High performance multilayer matt finish, with very low VOC content and extremely high wear and chemical resistance.
	
Product structure	Finish layer: WEARTOP® Veneered layer: Natural cork veneer Core layer: High-density agglomerated cork Edges: Square.
Installation	Glued according to installation instructions. Contact adhesion recommended - both tile backing and subfloor must be coated with suitable contact adhesive.

#### TECHNICAL DATA

Classification	EN 12104 / EN ISO 10874	23 Domestic Heavy. Residential areas with high traffic
Length and width	EN ISO 24342	600 x 300 mm ± 0.2%
Overall thickness	EN ISO 24346	4 mm ± 0.15 mm
Apparent density	ISO 3850	> 500 Kg/m <sup>3</sup>

# Naturals Fix

## GLUEDOWN CORK FLOOR TILES TECHNICAL SPECIFICATION

TECHNICAL DATA		
Mass per unit area	EN ISO 23997	2300 g/m <sup>2</sup>
Squareness and Straightness	EN ISO 24342	< 0.4 mm
Curling	EN ISO 23999	< 4 mm
Dimensional stability	EN ISO 23999	< 0.3%
Residual indentation	EN ISO 24343-1	< 0.3 mm
Castor chair	EN ISO 4918	No disturbance other than slight change in appearance and no delaminating
Simulated furniture leg movement	EN ISO 16581	No damage visible when tested with foot type 2
Abrasion resistance	EN 14354	> 5000 rev
Impact resistance (small ball)	EN 438-2	> 40 N
Scratch resistance	EN 438-2	Rating 2 (2.0 N)
Impact noise reduction	EN ISO 10140-3	$\Delta L_w = 14$ dB
Thermal resistance	EN 12667	0.05 m <sup>2</sup> .K/W
Light fastness	EN ISO 105-B02	5 (blue scale)
Slip resistance	EN 13893	Technical class DS $\mu > 0.30$
Reaction to fire	EN 13501-1	Class Dfl-s1
Formaldehyde emission	EN 14041	No formaldehyde-containing materials added during production
VOC emission	ISO 16000 parts 3, 6, 9	Fulfilled AgBB scheme Fulfilled French Classification A+

# Naturals Fix

## GLUEDOWN CORK FLOOR TILES TECHNICAL SPECIFICATION

GENERAL DATA	
Packaging	44 tiles per carton; 7.92 m <sup>2</sup> per carton; 54 cartons per pallet.
Underfloor heating	Suitable for hot-water and electrical underfloor heating. Maximum surface temperature 28°C.
Limited warranty	Surface finish will not wear through within 15 years (Residential) or 5 years (Commercial) under normal use with proper maintenance.
Environment	Made from more than 85% natural cork, a rapidly renewable resource. Contains no PVC and no softeners or substances hazardous to health or environment.



FSC® certified products are available upon request

GRANORTE reserves the right to make changes to material and structure to improve the quality or technical performance.

FSC® certified products are available upon request

Product data supplied by Granorte, Revestimentos de Cortica, Lda. | Av. Santiago, 68 | 4520-470 Rio Meao | Portugal | granorte.com

Granorte reserves the right to make changes to material and structure to improve quality or technical performance.